

Best choice for high volume tyre shops using efficient products.

NEW
P55 Plus



1100 mm

510 mm

75 Kg



COMING SOON



P55 Plus

www.giuliano-automotive.com

ELECTRONIC 3-D WHEEL-BALANCER WITH VIDEO DISPLAY, PNEUMATIC CLAMPING, LASER LINE AND LED LIGHT



Advanced software
for further upgrades*.

- Flat screen HD color video monitor 19" TFT. **Precise, reliable and easy to use** software.

FUNCTIONS

- Automatic measuring of wheel diameter and distance.
- Automatic START and STOP.
- Pneumatic wheel clamping.
- Static and dynamic balancing.
- OPTIMATCH function.
- Self-diagnosis and self-calibration.
- Optimization of static unbalance.
- CLIP system for application of stick-on weight.
- USB port for firmware updating via PC/notebook.
- Complete with wheel guard.

Available with **automatic** weight placement position **search function** (ref. P56 Plus).

LASER LINE

for exact positioning of adhesive weights.

LED LIGHT

to illuminate working area.

HIDDEN WEIGHT



- Fast & Easy Split (FES) function, is really the fastest method on the market to split balancing weights behind the spokes of your aluminum wheel.



A very practical **Wheel Lifter** reduces effort and increases productivity (optional).

- Two-position pedal.

Pneumatic wheel lock through pedal control.

- Automatic electric brake** in weight placement position.



Automatic wheel width measurement via **SONAR (TW)**, standard.




PNEUMATIC WHEEL CLAMPING



Complete with cones and pneumatic clamping system.



SPECIAL ALU-S PROGRAMS



Programs for selecting the best correction planes for any kind and shape of alloy rim.



SELF SELECTION MODE



Self-recognition of the Working program.



OPPOSITE WEIGHT FUNCTION (OPF) WITH LASER LINE



Laser Line function, enables to place the balancing stick-on weight on the lower inside part of the aluminum wheel (6 o'clock), easier and more accessible, by a Laser line indicator.

**The performance of the machine over time can improve, thanks to targeted updates.*

OPTIONAL ACCESSORIES



- Wheel clamping adaptors
- Clamping cones with spacers
- Wheel lifter

Find out more on our website !

STANDARD FEATURES

Max. wheel weight	75 kg
Max. wheel diameter	1100 mm
Rim diameter	10"-30" / 255-765 mm
Rim width	1,5"-20" / 40-510 mm
Power supply	230V 1ph (50/60) Hz
Unbalance detection time	4,7 s (5 3/4"x14") 15 kg
Balancing speed	< 150 rpm
Balancing precision	÷ 1 g
Operating pressure	8 - 10 bar (115-145 PSI)
Net weight with guard	112 Kg
Max. overall dimensions	1450x1150x1280+1540 mm

EXTENSIVE SELECTION OF STANDARD ACCESSORIES

STANDARD ACCESSORIES



- Wheel guard
- Set of 42-140 mm cones and **pneumatic** clamping system
- Manual gauge for measuring wheel rim width
- Counterweight pliers
- SONAR TW**