

Engineered for Precision. Built for Performance. Perfect for High-Volume Shops.

NEW
P58 Evo



COMING SOON



P58 Evo

www.giuliano-automotive.com

3-D WHEEL BALANCER WITH PROFESSIONAL DIAGNOSTICS, PNEUMATIC CLAMPING, TOUCHSCREEN DISPLAY, LASER LINE AND LED LIGHT



A very practical **Wheel Lifter** reduces effort and increases productivity (optional).



Advanced software for further upgrades*.

✓ 19" HD - Touchscreen-Display.

FUNCTIONS

- Automatic measuring of wheel diameter and distance.
- Automatic START and STOP.
- Pneumatic wheel clamping.
- Static and dynamic balancing.
- OPTIMATCH function.
- Self-diagnosis and self-calibration.
- Optimization of static unbalance.
- CLIP system for application of stick-on weight.
- USB port for firmware updating via PC/ notebook.
- Complete with wheel guard.

✓ **Automatic electric brake** in weight placement position.

✓ **Automatic positioning** in wheel weight placement.


✓ **Two-position pedal.**
Pneumatic wheel lock through pedal control.



✓ **Automatic wheel width measurement** using **SONAR TW** system.

✓ **LED LIGHT** to illuminate working area.

✓ **SPECIAL ALU-S PROGRAMS**




- Programs for selecting the best correction planes for any kind and shape of alloy rim.

✓ **HIDDEN WEIGHT**



- Fast & Easy Split (FES) function, is really the fastest method on the market to split balancing weights behind the spokes of your aluminum wheel.

✓ **OPPOSITE WEIGHT FUNCTION (OPF) WITH LASER LINE**



- Laser Line function helps position stick-on weights at 6 o'clock inside the aluminum wheel, guided by a precise laser indicator.

**The performance of the machine over time can improve, thanks to targeted updates.*

OPTIONAL ACCESSORIES



- Wheel clamping adaptors
- Clamping cones with spacers
- Wheel lifter

Find out more on our website !

STANDARD FEATURES

Max. wheel weight	75 kg
Max. wheel diameter	1100 mm
Rim diameter	10"-30" / 255-765 mm
Rim width	1,5"-20" / 40-510 mm
Power supply	230V 1ph (50/60) Hz
Cycle time	4,7 s (5 3/4"x14") 15 kg
Balancing speed	< 100 rpm
Balancing precision	÷ 0,5 g
Operating pressure	8 -10 bar (115-145 PSI)
Net weight with guard	117 kg
Max. overall dimensions	1530x1350x1360+1805 mm

STANDARD ACCESSORIES



- Wheel guard
- Set of 42-140 mm cones and pneumatic clamping system
- Manual gauge for measuring wheel rim width
- Counterweight pliers
- SONAR TW
- SONAR RRM