

TYRE-CHANGERS - TRUCKS & HEAVY DUTY

AUTOMATIC movements for easy and professional operation on heavy duty tyres.

For truck, bus and Agriculture tyres, professio-

5551 XLA



nal truck tyre service and high volume shops. Suitable for both tube and tubeless tyres.





You Tube Watch the video

Discover on our website!

AUTOMATIC HEAVY DUTY TRUCK TYRE CHANGER 14" - 46" / 58"



Suitable for control console installation on pivoting arm (optional).



Hydraulic movement

Hydraulic

movement



- Hydraulic travel movement of operating arm carriage (left-right).
- Operating arm and clamping chuck arm facing each other.
- Rim center hole clamping range ø 80 - 1200 mm.
- Clamping chuck minimum height from ground 315 mm (center).
- Wheel clamping by fully hydraulic operated jaws.

















Multistage clamping jaws

23by 5r





STANDARD FFATURES

	OIAIIDAIID I ENIOILEO	
	Rim clamping range w/o extensions	14" - 46"
	Rim clamping range with extensions (optional)	14" - 58"
	Max. tyre diameter	2300 mm (90,5")
	Max. tyre width	1100 mm (43")
	Bead breaker force	26350 N
	Operating pressure	130 bar (1885 Psi)
	Power supply	400V - 3ph / 2 speed *
	Hydraulic pump motor power	1,1 kW
	Clamping chuck motor power	1,3 / 1,8 kW
	Net weight	850 kg
	Max. tyre assembly weight	1500 kg
	Max. overall dimensions	2000÷2450x1800÷2250÷880x1840

Double tool (disk + finger) manual rotation.





- Emergency safety button on control console, for stopping all functions.
- Wide and low profiled platform eases the loading of heavy wheels.
- Designed, built and engineered in Italy.

Suitable for remote control installation (optional). Replaces standard cables and enables all functions control by radio transmission.



STANDARD ACCESSORIES



- Short bead lifting lever
- · Long bead lifting lever, for agriculture tyres
- . Mounting clamp for steel rims

MAIN OPTIONAL ACCESSORIES

Find out more on our website!









